Product Data Sheet

PDS-Peramin® SRA 10-EN

Peramin[®] SRA 10

Shrinkage reducer



Description

The drying shrinkage reducer Peramin® SRA 10 is a powder product based on polyols.

Peramin® SRA 10 is compatible with the majority of admixtures used in drymix mortars and specially with Peramin® CONPAC and SMF, but laboratory trials are advised before any industrial use.

Peramin[®] SRA 10 is recommended for powder formulations.

The fields of application are: dry mortar industry but not concrete applications according to **EUROCODE 2**

Typically, the dosage of Peramin® SRA 10 varies from 1 - 5 % by weight of binder.

Before use, it's recommended to read the safety data sheet.



Specification

Peramin[®] SRA 10 is produced and controlled within a quality management system that is certified according to ISO 9001.

The specification limits define the absolute limits of product conformity applicable for individual values.

The usual range represents typical values of production. This information is given for guidance only.

Chemical composition

Main constituents (%)

| | Usual range | Specification limit |
|-----------------------------|-------------|---------------------|
| Active content, % by weight | | 65 - 71 |

Other constituents, (%)

| | Usual range | Specification limit |
|-------------------|-------------|---------------------|
| pH in 5% solution | | 6 - 8 |

The chemical characteristics of Peramin® SRA 10 are determined according to calibrated internal methods.

Fineness

| Residue at, % | Usual range | Specification limit |
|---------------|-------------|---------------------|
| 600 µm | | < 5 |

Measurements made by sieving.



Additional information

This information is given for guidance only.

Other physical characteristics

Bulk density: 350 - 430 kg/m³

Visual aspect / Appearance

White powder



Shelf life and packaging

For optimal performance, Peramin® SRA 10 should be stored in its original packaging, in dry conditions at 5 - 40°C and not in direct contact with the ground. When stored in these conditions, performance is guaranteed for a minimum of 12

Peramin® SRA 10 is available in pallets of 20 bags of 25 kg.

Peramin warrants that the products comply with the specifications stated herein to the exclusion of any other warranty, express or implied. Peramin makes no representation or warranty of any kind, either express or implied, as to the merchantability or fitness for a particular purpose or use of the products.

The warranty shall be limited to the replacement of the non-conforming products or, at Peramin's option, the refund of the purchase price.

Any technical advice, recommendations or information are given based on Peramin's current knowledge and experience of the products and are deemed to be accurate. However, Peramin undertakes no liability or responsibility of any kind in respect thereof. Users are invited to check that they have the latest version of this document

